

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**FLOOR SERVICE Teak- und Gartenmöbelöl**

Revision date: 27.04.2022

Product code: OV-652

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

FLOOR SERVICE Teak- und Gartenmöbelöl

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Vegetable resin paints

**1.3. Details of the supplier of the safety data sheet**

Company name:	Overmat Industries B.V.	
Street:	Scharlo 11	
Place:	NL-5165 Waspik	
Telephone:	+31-(0)416-31 77 88	Telefax: +31-(0)416-31 35 61
e-mail:	info@overmat.nl	
e-mail (Contact person):	info@overmat.nl	
Internet:	www.overmat.nl	

**1.4. Emergency telephone number:**

+31-(0)416-31 77 88

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**P273 Avoid release to the environment.  
P501 Dispose of contents/container to an appropriate recycling or disposal facility.**Special labelling of certain mixtures**EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction.**2.3. Other hazards**

Spontaneous ignition possible through autoxidation of cloths soaked in the product.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### FLOOR SERVICE Teak- und Gartenmöbelöl

Revision date: 27.04.2022

Product code: OV-652

Page 2 of 8

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Isoalkane C11-C14			40-50 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304			
22464-99-9	Zirconium octoate			0,1-1 %
	245-018-1		01-2119979088-21	
	Skin Irrit. 2; H315			
13434-24-7	manganese octoate			0,1-0,5 %
	236-562-0			
	Skin Irrit. 2; H315			
55406-53-6	Iodo-2-propynyl-butylcarbamate			0,6 %
	259-627-5			
	Acute Tox. 3, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H331 H302 H318 H317 H372 H400 H410			
85203-81-2	Zinc octoate			0,1-1 %
	286-272-3		01-2119979093-30	
	Repr. 2, Eye Irrit. 2, Aquatic Chronic 3; H361d H319 H412			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
55406-53-6	259-627-5	Iodo-2-propynyl-butylcarbamate	0,6 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 500 mg/kg	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

- When in doubt or if symptoms are observed, get medical advice.
- Never give anything by mouth to an unconscious person or a person with cramps.
- If unconscious but breathing normally, place in recovery position and seek medical advice.

##### After inhalation

- Remove casualty to fresh air and keep warm and at rest.
- If breathing is irregular or stopped, administer artificial respiration.

##### After contact with skin

- Immediately remove any contaminated clothing, shoes or stockings.
- After contact with skin, wash immediately with plenty of water and soap.
- Do not wash with: Solvents/Thinner

##### After contact with eyes

- In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.
- Seek medical advice immediately.

##### After ingestion

- If swallowed, rinse mouth with water (only if the person is conscious).

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**FLOOR SERVICE Teak- und Gartenmöbelöl**

Revision date: 27.04.2022

Product code: OV-652

Page 3 of 8

Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.  
Do NOT induce vomiting.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water mist**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure.

Use appropriate respiratory protection.

**5.3. Advice for firefighters**

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking. Ventilate affected area.

Avoid breathing dust/fume/gas/mist/vapours/spray.

See protective measures under point 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****Other information**

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal. Disposal: see section 13

Clean with detergents. Avoid solvent cleaners.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away.

Use explosion-proof electrical equipment. Filling and transfer: Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**FLOOR SERVICE Teak- und Gartenmöbelöl**

Revision date: 27.04.2022

Product code: OV-652

Page 4 of 8

**Advice on protection against fire and explosion**

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

**Hints on joint storage**

Do not store together with: Oxidising agent, Strong acid, Strong alkali

**Further information on storage conditions**

Follow the instructions for use on the label.

storage temperature of °C 5 up to °C 30.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

**7.3. Specific end use(s)****SECTION 8: Exposure controls/personal protection****8.1. Control parameters****8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear eye/face protection.

**Hand protection**

Wear suitable gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. See information supplied by the manufacturer.

Suitable material: Nitrilkautschuk

Breakthrough time: >= 8 hmin.

Use protective skin cream before handling the product.

**Skin protection**

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

**Respiratory protection**

Respiratory protection necessary at: exceeding exposure limit values.

Use suitable breathing apparatus.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	flüssig
Colour:	bräunlich
Odour:	mild, nach Ölen und Wachsen

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### FLOOR SERVICE Teak- und Gartenmöbelöl

Revision date: 27.04.2022

Product code: OV-652

Page 5 of 8

#### Test method

#### Changes in the physical state

Melting point/freezing point:	n.a.
Boiling point or initial boiling point and boiling range:	> 180 °C
Sublimation point:	n.a.
Softening point:	n.a.
Pour point:	n.a.
:	n.a.
Flash point:	> 61 °C DIN 53213

#### Flammability

Solid/liquid:	n.a.
Gas:	n.a.
Lower explosion limits:	0,6 g/m <sup>3</sup>
Upper explosion limits:	7,0 g/m <sup>3</sup>

#### Self-ignition temperature

Solid:	n.a.
Gas:	n.a.

Viscosity / kinematic: > 20,5 mm<sup>2</sup>/s  
(at 40 °C)

Flow time: > 60 s 3 DIN EN ISO 2431  
(at 40 °C)

Water solubility: n.a.

Partition coefficient n-octanol/water: n.a.

Density (at 20 °C): 0,87 g/cm<sup>3</sup> DIN 53217

Bulk density: n.a.

Relative vapour density: n.a.

#### 9.2. Other information

##### Information with regard to physical hazard classes

Sustaining combustion: Not sustaining combustion UN Test L.2

##### Other safety characteristics

Solvent content: 420 g/l

Evaporation rate: n.a.

##### Further Information

### SECTION 10: Stability and reactivity

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

#### 10.4. Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

#### 10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**FLOOR SERVICE Teak- und Gartenmöbelöl**

Revision date: 27.04.2022

Product code: OV-652

Page 6 of 8

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
55406-53-6	Iodo-2-propynyl-butylcarbamate				
	oral	ATE 500 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			

**Practical experience**

Following inhalation:

Potential hazards: May cause respiratory irritation. Depression of central nervous system.

Symptoms: Headache, Dizziness, Dizziness, Unconsciousness

After eye contact:

Irritating to eyes. (reversible.)

Following ingestion:

Symptoms: Nausea, Vomiting, Gastrointestinal complaints

Following skin contact:

The product is skin resorptive. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**Further information**

There are no data available on the mixture itself.

Reference to other sections: 2, 3

**SECTION 12: Ecological information****12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Further information**

There are no data available on the mixture itself.

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.

Dispose according to legislation.

**List of Wastes Code - residues/unused products**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### FLOOR SERVICE Teak- und Gartenmöbelöl

Revision date: 27.04.2022

Product code: OV-652

Page 7 of 8

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - used product**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**Contaminated packaging**

Completely emptied packages can be recycled.  
Dispose according to legislation.

#### SECTION 14: Transport information

**Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No dangerous good in sense of this transport regulation.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

#### SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2004/42/EC (VOC):	420 g/l : Kategorie f
Subcategory according to Directive	Interior and exterior minimal build woodstains - Solvent-borne coatings,
2004/42/EC:	VOC limit value: 700 g/l

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### FLOOR SERVICE Teak- und Gartenmöbelöl

Revision date: 27.04.2022

Product code: OV-652

Page 8 of 8

#### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

#### Additional information

Observe in addition any national regulations!

### SECTION 16: Other information

#### Classification for mixtures and used evaluation method according to regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*