

					THE FLOOR TECHNICIANS
Article Print o Versio	date:	34080 - 34082 21.08.2023 1.12	Floorservice Natur Revision date: 01. Issue date: 01.06.2) 14359 EN Page 1 / 9
SEC	TION 1: I	dentification of th	e substance/mixtu	ure and of the compa	ny/undertaking
1.1.	Product i	dentifier			
		. (manufacturer/sup ne/designation	plier)	34080 - 34082 Floorservice Nature Pr UFI: U600-S0KH-H006	
1.2.		identified uses of t identified uses	the substance or mix	xture and uses advised	against
1.3.	Details of	f the supplier of the	e safety data sheet		
	supplier	(manufacturer/imp	orter/downstream us	ser/distributor)	
	Scharlo 1			+31 (0) 416 / 317788	
	NL-5165	NG Waspik		info@overmat.nl	
	-			www.overmat.nl	
	Product S	ent responsible for afety Department 8: ompetent person)		Peter Kerstens +31 (0) 416 / 317788 p.kerstens@overmat.n	I
1.4.	Emergen	cy telephone numb	per	Netherland +31(030) 2	748888
SEC	TION 2: F	lazards identifica	tion		
2.1.	Classifica	ation of the substa	nce or mixture		
	Classific	ation according to	Regulation (EC) No	1272/2008 [CLP]	
	The mixtu	re is classified as ha	-	regulation (EC) No 1272	2/2008 [CLP].
	Skin Sens STOT SE	<. 4 / H332 5. 1 / H317 3 / H335 hronic 3 / H412	Acute toxicity (inha Respiratory or skin STOT-single expos Hazardous to the a	sensitisation	Harmful if inhaled. May cause an allergic skin reaction. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.
2.2.	Label ele			quallo onvironmont	
			ulation (EC) No. 1272	2/2008 [CLP]	
	Hazard p	ictograms			
		Warning			
	Hazard s H332	tatements	ıl if inhaled.		
	H317 H335	May ca	iuse an allergic skin ro iuse respiratory irritati		
	H412		It to aquatic life with lo		
	P280		protective gloves and		
	P302 + P3 P405 P501	Keep lo	ocked up.	ity of soap and water. er to industrial incineratio	n plant.
	Hazard c	omponents for labe	elling		e glycol mono-Me ether-blocked
	Supplem EUH204	ental hazard inforn Contair		produce an allergic reacti	on.
2.3.	Other ha	zards			



Article No.:	34080 - 34082	Floorservice Nature Protect Premium 2K (B)	
Print date:	21.08.2023	Revision date: 01.06.2023	14359 EN
Version:	1.12	Issue date: 01.06.2023	Page 2 / 9

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

- · · ·			
Classification ad	ccording to Regulation (EC) No 1272/2008 [CLP]		
EC No.	REACH No.		
CAS No.	Designation	weight-%	
Index No.	g		
679-501-7 160994-68-3	Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me	50 < 100	
	ether-blocked		
	Acute Tox. 4 H332 / Skin Sens. 1B H317 / STOT SE 3 H335 / Aquatic Chronic 3 H412		

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Remove affected person from the danger area and lay down.

Put victim at rest, cover with a blanket and keep warm.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Move victim to fresh air.

In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Take off immediately all contaminated clothing.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious but breathing normally, place in recovery position and seek medical advice.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In all cases of doubt, or when symptoms persist, seek medical advice.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap.

Do not use solvents or thinners. Call a physician immediately.

Wash contaminated clothing prior to re-use.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Following ingestion

Rinse mouth immediately and drink plenty of water. Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Never give anything by mouth to an unconscious person or a person with cramps.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Symptoms

May irritate eyes. May cause respiratory irritation. May irritate skin. May cause sensitization by skin contact.



Article No.:	34080 - 34082	Floorservice Nature Protect Premium 2K (B)	
Print date:	21.08.2023	Revision date: 01.06.2023	14359 EN
Version:	1.12	Issue date: 01.06.2023	Page 3 / 9

Special treatment

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. In case of fire may be liberated: carbon monoxide, carbon dioxide, Nitrogen oxides (NOx), Isocyanates. Possible in traces: Hydrogen cyanide (hydrocyanic acid).

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Wear full chemical protective clothing. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

Keep people away from and upwind of spill/leak.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8. Avoid contact with eyes and skin. Remove persons to safety. Wear suitable protective clothing. Keep away from heat. - No smoking. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

Methods and material for containment and cleaning up 6.3.

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Use appropriate container to avoid environmental contamination. Fouled surfaces must be immediately cleaned with suitable solvents, Useable as such (flammable): water 45 vol.% ethanol or i-propanol 50 vol. % ammonia solution (density= 0.88) 5 vol.%

Alternative (non-flammable): sodium carbonate 5 vol.% water 95 vol.%.

Take up spilled residuals with the same agent and leave them for a few days in unclosed containers until there is no further reaction. Then, close the containers and dispose of them in accordance with the regulations for waste removal (refer to section 13).

Provide adequate ventilation.

6.4. Reference to other sections

SECTION 7: Handling and storage SECTION 8: Exposure controls/personal protection **SECTION 13: Disposal considerations**

SECTION 7: Handling and storage

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

People who spray this preparation should have regular pulmonary function tests.

7.1. Precautions for safe handling

Advices on safe handling

Keep away from heat sources, sparks and open flames. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment



Article No.:	34080 - 34082	Floorservice Nature Protect Premium 2K (B)	
Print date:	21.08.2023	Revision date: 01.06.2023	14359 EN
Version:	1.12	Issue date: 01.06.2023	Page 4 / 9

must be protected meeting the accepted standard. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations. Protect from sunlight.

Keep away from food, drink and animal feedingstuffs.

Take off immediately all contaminated clothing.

Separate storage of work clothes.

Wash hands before breaks and after work.

Handle in accordance with good industrial hygiene and safety practice.

Further information

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from: Oxidizing agent, Acids, Alkali (Iye), Amines, Alcohols, Reducing agent. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

People who spray this preparation should have regular pulmonary function tests.

8.1. Control parameters

Occupational exposure limit values

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. When spraying, wear self-contained breathing apparatus. For other tasks a suitable respiratory system must be used, if local and room suction is not sufficient for keeping aerosol and solvent vapour concentration below the exposure limit values. (refer to Personal protection equipment.)

Personal protection equipment

Respiratory protection

If the pollutant concentration is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used.

Use only respiratory protection equipment with CE-symbol including four digit test number.

respirator with A/P-filter (EN 14387)

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing.



Article No.:	34080 - 34082	Floorservice Nature Protect Premium 2K (B)
Print date:	21.08.2023	Revision date: 01.06.2023
Version:	1.12	Issue date: 01.06.2023

14359 EN Page 5 / 9

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with eyes and skin. Do not breathe vapour/aerosol. Keep away from food, drink and animal feedingstuffs. Take off immediately all contaminated clothing. Separate storage of work clothes. When using do not eat, drink or smoke. Wash hands before breaks and after work. Guarantee that the eye flushing systems and safety showers are closely located to the working place.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Colour:colourlessOdour:characteristicOdour threshold:not determinedMelting point/freezing point:not applicableInitial boiling point and boiling range:not determinedInitial boiling point and boiling range:not determinedFlammability:Combustible liquid.Lower and upper explosion limit:Combustible liquid.Lower explosion limit:not determinedUpper explosion limit:not determinedFlash point:> 60 °CMethod:ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determinedpH at 20 °C:not applicable
Odour threshold:not determinedMelting point/freezing point:not applicableInitial boiling point and boiling range:not determinedFlammability:Combustible liquid.Lower and upper explosion limit:not determinedUpper explosion limit:not determinedFlash point:> 60 °CMethod:ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Melting point/freezing point:not applicableInitial boiling point and boiling range:not determinedInitial boiling point and boiling range:not determinedFlammability:Combustible liquid.Lower and upper explosion limit:not determinedLower explosion limit:not determinedUpper explosion limit:not determinedFlash point:> 60 °CMethod:ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Initial boiling point and boiling range:not determinedInitial boiling point and boiling range:not determinedFlammability:Combustible liquid.Lower and upper explosion limit:not determinedUpper explosion limit:not determinedFlash point:> 60 °CMethod:ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Flammability:Combustible liquid.Lower and upper explosion limit:not determinedLower explosion limit:not determinedUpper explosion limit:not determinedFlash point:> 60 °CMethod:ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Lower and upper explosion limit:not determinedLower explosion limit:not determinedUpper explosion limit:not determinedFlash point:> 60 °CMethod:ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Lower explosion limit:not determinedUpper explosion limit:not determinedFlash point:> 60 °CMethod:ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Upper explosion limit:not determinedFlash point:> 60 °CMethod:ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Flash point:> 60 °C Method: ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Auto-ignition temperature:Method: ASTM D 7094aAuto-ignition temperature:not determinedDecomposition temperature:not determined
Decomposition temperature: not determined
pH at 20 °C: not applicable
pH at 20 °C: not applicable
• • • • • • • • • • • • • • • • • • • •
Cinematic viscosity (40°C): < 80 mm²/s
Viscosity at °C: 18-22 s 4mm
Solubility(ies):
Water solubility at 20 °C: partially soluble
Partition coefficient: n-octanol/water: see section 12
Vapour pressure at 20 °C: not determined
Density and/or relative density:
Density at 20 °C: 1,07 g/cm ³
Relative vapour density: not determined
particle characteristics: not applicable
9.2. Other information
Solid content: 62,50 weight-%
solvent content:
Organic solvents: 37,50 weight-%
Water: 0,00 weight-%

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.



Article No.:	34080 - 34082	Floorservice Nature Protect Premium 2K (B)	
Print date:	21.08.2023	Revision date: 01.06.2023	14359 EN
Version:	1.12	Issue date: 01.06.2023	Page 6 / 9

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures. Further remarks: SECTION 7: Handling and storage

10.3. Possibility of hazardous reactions

Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

Alkali (lye), Oxidizing agent, Acids, Amines, Alcohols, Reducing agent

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, Nitrogen oxides (NOx), Isocyanates.

Possible in traces: Hydrogen cyanide (hydrocyanic acid).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Floorservice Härter für Nature Protect Premium 2K Sealer Premium 2K oral, LD50, Rat: > 2000 mg/kg By analogy. dermal, LD50, Rat: > 2000 mg/kg By analogy. Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked

oral, LD50, Rat: > 2000 mg/kg dermal, LD50, Rat: > 2000 mg/kg Method: OECD 402

Skin corrosion/irritation; Serious eye damage/eye irritation

Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked Skin, Rabbit Method: OECD 404 mild irritant.
eyes, Rabbit Method: OECD 405 mild irritant.
Respiratory or skin sensitisation

May cause an allergic skin reaction.

Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked Skin, Guinea pig:

Method: OECD 406 sensitising

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked Germ cell mutagenicity Ames test negative.

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Splashing may cause eye irritation and reversible damage. The fractions of acrylic resin in the preparation have an irritant effect. Prolonged or repeated contact with the preparation can lead to irritations of mucous membranes and of skin such as redness,



Article No.:	34080 - 34082	Floorservice Nature Protect Premium 2K (B)	
Print date:	21.08.2023	Revision date: 01.06.2023	143
Version:	1.12	Issue date: 01.06.2023	Pag

14359 EN Page 7 / 9

formation of blebs, dermatitis, etc..

Cases of allergic skin reactions have been observed.

Liquid splashes can lead to irritations of the eyes.

Ingestion may cause nausea, weakness and affect the central nervous system.

Because of the isocyanate components' properties of this and with consideration of similar preparations the following applies: This mixture may cause acute irrtation and/or sensitization of airways which lead to tightness in thorax, short-breath and asthmatic complaints. After sensitization even concentrations below the exposure limit values may cause asthma. Repeated inhaling can lead to permanent illness of the respiratory tract.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked Fish toxicity, LC50, Danio rerio (zebrafish): 28,3 mg/L (96 h) Method: OECD 203

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked Biodegradation: 2 % (28 d) Method: OECD 301F Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available. 12.7. **Other adverse effects**

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. Handle contaminated packages in the same way as the substance itself. Do not dispose of with domestic refuse.

This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances *Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package



Article No.:	34080 - 34082	Floorservice Nature Protect Premium 2K (B)	
Print date:	21.08.2023	Revision date: 01.06.2023	14359 EN
Version:	1.12	Issue date: 01.06.2023	Page 8 / 9

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. Empty container completely.

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

	No dangerous good in sense of this transport regulation.		
14.1.	UN number or ID number		
		not applicable	
14.2.	UN proper shipping name		
1/1 3	Transport hazard class(es)		
14.0.		not applicable	
14.4.	Packing group		
		not applicable	
14.5.	Environmental hazards		
	Land transport (ADR/RID)	not applicable	
	Marine pollutant	not applicable	

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

EmS-No.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 393,225

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:					
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.			
Skin Sens. 1B / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.			
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.			
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.			
Classification procedure					

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]					
Acute Tox. 4	Acute toxicity (inhalative)	Calculation method.			
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.			
STOT SE 3	STOT-single exposure	Calculation method.			



	24000	0.4000 EI	Flooren vice Network Protect Promium 2K (P)		THE FLOOR TECHNICIANS			
Article No.: Print date: Version:	34080 - 21.08.20 1.12	023 Re	oorservice Nature Protect Premium 2K (l evision date: 01.06.2023 sue date: 01.06.2023	в)	14359 EN Page 9 / 9			
Aqu	atic Chronic 3	Ha	zardous to the aquatic environment	Calculation m	nethod.			
Abb	reviations and a	acronyms						
ADF	ADR European Agreement concerning the International Carriage of Dangerous Goods by F							
OEL	<u>-</u>	Occupational Exposure Limit Value						
BLV		Biological Limit Value						
CAS		Chemical Abstracts Service						
CLP		Classification, Labelling and Packaging						
CMF								
DIN		German Institute for Standardization / German industrial standard						
DNE		Derived No-Effect Level						
EAK	XV	European Waste Catalogue Directive						
EC		Effective Concentration						
EC		European Community						
EN		European Standard International Air Transport Association – Dangerous Goods Regulations						
	A-DGR							
-	Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in B						
ICA	ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Da		the Safe Transport of Dangerous					
		Goods by Air						
IND	G Code	International Maritime Code for Dangerous Goods						
LC		International Organization for Standardization Lethal Concentration						
LD								
	RPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships						
OEC	-	Organisation for Economic Cooperation and Development						
PBT		persistent, bioaccumulative, toxic						
PNE		Predicted No Effect Concentration						
REA	-	Registration, Evaluation, Authorisation and Restriction of Chemicals						
RID		Regulations concerning the International Carriage of Dangerous Goods by Rail						
UN		United Nations						
VOC)	Volatile Organic Compounds						
vPvI			ent and very bioaccumulative					
			-					

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.