



Product information

Prime Weathered Grey

An all new technology where Prime Weathered Grey, a product to achieve a special aged and greyish effect on oak wood, in combination with the existing range of colours from the Floorservice assortment offers many fresh and surprising new colour effects.

Floorservice Prime Weathered Grey has been developed to create that typical aged and greyish effect on oak wood. The possibilities are countless and this, combined with a top coat of either colour within our range of Floorservice Hardwax-oil Classic, Pro or Profiline, leads to various creative and commercially interesting colour options.

Characteristics

Floorservice Prime Weathered Grey is a pre-treatment product for aging wood.

Application

On raw untreated tannin-containing wooden objects of oak or larch.

Technical information

Surface: Has to be dry, clean and free of grease.

Processing temperature: 15 – 35c at 65% relative humidity.

Drying time: At 20°C and 65% RH Depending on ventilation: min. 6 HRS.

After drying de-nib the surface by using a Bordeaux pad (remove fibres and salts).

Do not use pad for more than approx.. 40sqm (using both sides).

Usage: 4-8sqm / litre, heavily depending on application method and surface.

Cleaning of tools: with water. **Storage:** Frost free storage!

Safety advise: Please see our safety data sheet: FLS PWG. **Density (20°C):** 1,00 – 1,02 kg/L method: DIN 53217

Flashpoint: Non-flammable.

Packing: 20 Litres Shelf life: 6 Months

Application advise

Apply Floorservice Prime Weathered Grey evenly by nebulizing onto the surface. After 30 seconds of contact, equalize the moisturized parts with a non-linting cloth or mop. NOTE!: By overlapping, using too little product or spilling droplets onto the wood, uneven discolouration is possible.

Above product information and advice is non-binding and based on extensive testing and experience. Due to the various manners of application possible and other factors we have no influence over, we cannot be held responsible.

We therefore always advise to test prior when in doubt.

27.06.2017





Overmat Industries b.v. Scharlo 11 | NL-5165 NG Waspik | The Netherlands | Tel: +31 (0) 416 31 77 88 | Internet: www.overmat.nl